

# HEAVY-DUTY IMPACT WRENCHES



2934B2



2940B2



2950B7

## Heavy-Duty Impact Wrenches

Features a twin hammer clutch for more power per pound, a pressure fed clutch lubrication system, two piece motor housing for easy maintenance and a built-in muffler for low noise and direct drive for fast run down. Parts are interchangeable with Ingersoll-Rand 2934, 2940 and 2950 series impact wrenches.

Model No.	Drive	Max Torque	Free Speed	Handle Trigger Type	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
2934B2 2934A2 2934B1 2934A1	1" Sq. Thru-Hole 1" Sq. Thru-Hole #5 Spline #5 Spline	1100-1500 ft-lbs	6600 rpm	Inside Outside Inside Outside	11-1/4"	19 lbs	1/2"	3/4"	47 cfm
2940B2 2940A2 2940B1 2940A1	1" Sq. Thru-Hole 1" Sq. Thru-Hole #5 Spline #5 Spline	1600-2000 ft-lbs	5000 rpm	Inside Outside Inside Outside	12-13/32"	22 lbs	1/2"	3/4"	58 cfm
2950B7 2950A7 2950B1 2950A1	1-1/2" Sq. Thru-Hole 1-1/2" Sq. Thru-Hole #5 Spline #5 Spline	2500-3000 ft-lbs	3750 rpm	Inside Outside Inside Outside	14-1/2"	33 lbs	1/2"	3/4"	70 cfm